

# Habbig HS650 Tree Cutter

...part of our Waterway Maintenance range



Habbig tree cutters have been manufactured in Germany for over **20 years**, providing high quality and robust tree cutting attachments for excavators and similar machinery.

Hundreds of Habbig tree cutters have been supplied in the UK and Ireland by exclusive distributor, Aquatic Control Engineering Ltd since 1996, to public environmental sectors, rail and other specialised contractors.

Habbig tree cutters are designed to fulfil one simple purpose; higher felling capacities with increased workplace health and safety. All Habbig tree cutters allow the operator to cut and grab timber from within the cab of an excavator and safely, quickly and neatly clear large volumes of branches and trunks. The timber can even be placed exactly where required.



The Habbig HS650 is the smaller cutter in the range providing a light weight and hassle free approach to tree cutting for embankment maintenance. This model is particularly suited to lighter maintenance schedules or where smaller excavators are used.

## Design Benefits and Features

### Versatility

The HS650 model can be manufactured with an integrated swivel (HS650 SE), allowing rotation of 55 degrees in either direction when mounted on an excavator.

### Resting Bracket

This cost effective model features an additional frame support at the top, allowing tree lengths to rest against it. This is designed to allow for cutting efficiencies and increased operator safety without compromising on size and weight.

## Technical Specification

Length	1350mm
Width	800mm
Height	1100mm
Weight	270kg
Opening span	550mm
Max. Working Load	700kg
Cutting dia. Soft wood	200mm
Cutting dia. Hard wood	160mm
Max. Cut Length	3 m
Hydraulic RAM: cutters	60l/m-100l/m 200 bar
<b>Recommended Excavator size is 3-7 ton</b>	



## Aquatic Control Engineering Ltd

Ph: 01777 249080  
[www.aquaticcontrol.co.uk](http://www.aquaticcontrol.co.uk)

**Head Office**  
 Hall Farm  
 Main Street  
 Rampton  
 Retford  
 Nottinghamshire  
 DN22 0HR